

SATELLITE COMMUNICATIONS SYSTEMS

Systems, Techniques and Technology

Fifth Edition

Gérard Maral

*Ecole Nationale Supérieure des Télécommunications,
Site de Toulouse, France*

Michel Bousquet

*Ecole Nationale Supérieure de l'Aéronautique et de l'Espace (SUPAERO),
Toulouse, France*

*Revisions to fifth edition by **Zhili Sun**
University of Surrey, UK*

*with contributions from Isabelle Buret,
Thales Alenia Space*



A John Wiley and Sons, Ltd, Publication

SATELLITE COMMUNICATIONS SYSTEMS

Fifth Edition

SATELLITE COMMUNICATIONS SYSTEMS

Systems, Techniques and Technology

Fifth Edition

Gérard Maral

*Ecole Nationale Supérieure des Télécommunications,
Site de Toulouse, France*

Michel Bousquet

*Ecole Nationale Supérieure de l'Aéronautique et de l'Espace (SUPAERO),
Toulouse, France*

*Revisions to fifth edition by **Zhili Sun**
University of Surrey, UK*

*with contributions from Isabelle Buret,
Thales Alenia Space*



A John Wiley and Sons, Ltd, Publication

Copyright © 1986, 1993, 1998, 2002
This edition first published 2009
© 2009 John Wiley & Sons Ltd.

Registered office

John Wiley & Sons Ltd, The Atrium, Southern Gate, Chichester, West Sussex, PO19 8SQ, United Kingdom

For details of our global editorial offices, for customer services and for information about how to apply for permission to reuse the copyright material in this book please see our website at www.wiley.com.

The right of the author to be identified as the author of this work has been asserted in accordance with the Copyright, Designs and Patents Act 1988.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, except as permitted by the UK Copyright, Designs and Patents Act 1988, without the prior permission of the publisher.

Wiley also publishes its books in a variety of electronic formats. Some content that appears in print may not be available in electronic books.

Designations used by companies to distinguish their products are often claimed as trademarks. All brand names and product names used in this book are trade names, service marks, trademarks or registered trademarks of their respective owners. The publisher is not associated with any product or vendor mentioned in this book. This publication is designed to provide accurate and authoritative information in regard to the subject matter covered. It is sold on the understanding that the publisher is not engaged in rendering professional services. If professional advice or other expert assistance is required, the services of a competent professional should be sought.

Library of Congress Cataloging-in-Publication Data

Maral, Gérard.

[Systèmes de télécommunications par satellites. English]

Satellite communications systems / Gérard Maral, Michel Bousquet. — 5th ed.

p. cm.

Includes bibliographical references and index.

ISBN 978-0-470-71458-4 (cloth)

1. Artificial satellites in telecommunication. I. Bousquet, Michel. II. Title.

TK5104.M3513 2009

621.382'5—dc22

2009023579

A catalogue record for this book is available from the British Library.

ISBN 978-0-470-71458-4 (H/B)

Typeset in 9/11 pt Palatino by Thomson Digital, Noida, India.

Printed in Singapore by Markono Print Media Pte Ltd.

This book is printed on acid-free paper responsibly manufactured from sustainable forestry, in which at least two trees are planted for each one used for paper production.

Original translation into English by J.C.C. Nelson.

CONTENTS

ACKNOWLEDGEMENT	xv
ACRONYMS	xvii
NOTATION	xxv
1 INTRODUCTION	1
1.1 Birth of satellite communications	1
1.2 Development of satellite communications	1
1.3 Configuration of a satellite communications system	3
1.3.1 Communications links	4
1.3.2 The space segment	5
1.3.3 The ground segment	8
1.4 Types of orbit	9
1.5 Radio regulations	12
1.5.1 The ITU organisation	12
1.5.2 Space radiocommunications services	13
1.5.3 Frequency allocation	13
1.6 Technology trends	14
1.7 Services	15
1.8 The way forward	17
References	18
2 ORBITS AND RELATED ISSUES	19
2.1 Keplerian orbits	19
2.1.1 Kepler's laws	19
2.1.2 Newton's law	19
2.1.3 Relative movement of two point bodies	20
2.1.4 Orbital parameters	23
2.1.5 The earth's orbit	28
2.1.6 Earth-satellite geometry	35
2.1.7 Eclipses of the sun	41
2.1.8 Sun-satellite conjunction	42
2.2 Useful orbits for satellite communication	43
2.2.1 Elliptical orbits with non-zero inclination	43
2.2.2 Geosynchronous elliptic orbits with zero inclination	54
2.2.3 Geosynchronous circular orbits with non-zero inclination	56
2.2.4 Sub-synchronous circular orbits with zero inclination	59
2.2.5 Geostationary satellite orbits	59

2.3	Perturbations of orbits	68
2.3.1	The nature of the perturbations	69
2.3.2	The effect of perturbations; orbit perturbation	71
2.3.3	Perturbations of the orbit of geostationary satellites	73
2.3.4	Orbit corrections: station keeping of geostationary satellites	81
2.4	Conclusion	97
	References	97
3	BASEBAND SIGNALS AND QUALITY OF SERVICE	99
3.1	Baseband signals	99
3.1.1	Digital telephone signal	100
3.1.2	Sound signals	103
3.1.3	Television signals	104
3.1.4	Data and multimedia signals	107
3.2	Performance objectives	108
3.2.1	Telephone	108
3.2.2	Sound	108
3.2.3	Television	108
3.2.4	Data	108
3.3	Availability objectives	109
3.4	Delay	111
3.4.1	Delay in terrestrial network	111
3.4.2	Propagation delay over satellite links	111
3.4.3	Baseband-signal processing time	112
3.4.4	Protocol-induced delay	112
3.5	Conclusion	112
	References	113
4	DIGITAL COMMUNICATIONS TECHNIQUES	115
4.1	Baseband formatting	115
4.1.1	Encryption	115
4.1.2	Scrambling	117
4.2	Digital modulation	118
4.2.1	Two-state modulation—BPSK and DE-BPSK	119
4.2.2	Four-state modulation—QPSK	120
4.2.3	Variants of QPSK	121
4.2.4	Higher-order PSK and APSK	124
4.2.5	Spectrum of unfiltered modulated carriers	125
4.2.6	Demodulation	125
4.2.7	Modulation spectral efficiency	130
4.3	Channel coding	131
4.3.1	Block encoding and convolutional encoding	132
4.3.2	Channel decoding	132
4.3.3	Concatenated encoding	133
4.3.4	Interleaving	134
4.4	Channel coding and the power–bandwidth trade-off	135
4.4.1	Coding with variable bandwidth	135
4.4.2	Coding with constant bandwidth	137
4.4.3	Example: Downlink coding with on-board regeneration	139
4.4.4	Conclusion	139

4.5	Coded modulation	140
4.5.1	Trellis coded modulation	141
4.5.2	Block coded modulation	144
4.5.3	Decoding coded modulation	145
4.5.4	Multilevel trellis coded modulation	145
4.5.5	TCM using a multidimensional signal set	146
4.5.6	Performance of coded modulations	146
4.6	End-to-end error control	146
4.7	Digital video broadcasting via satellite (DVB-S)	148
4.7.1	Transmission system	148
4.7.2	Error performance requirements	152
4.8	Second generation DVB-S	152
4.8.1	New technology in DVB-S2	153
4.8.2	Transmission system architecture	154
4.8.3	Error performance	156
4.9	Conclusion	157
4.9.1	Digital transmission of telephony	157
4.9.2	Digital broadcasting of television	159
	References	160
5	UPLINK, DOWNLINK AND OVERALL LINK PERFORMANCE; INTERSATELLITE LINKS	163
5.1	Configuration of a link	163
5.2	Antenna parameters	164
5.2.1	Gain	164
5.2.2	Radiation pattern and angular beamwidth	165
5.2.3	Polarisation	168
5.3	Radiated power	170
5.3.1	Effective isotropic radiated power (EIRP)	170
5.3.2	Power flux density	170
5.4	Received signal power	171
5.4.1	Power captured by the receiving antenna and free space loss	171
5.4.2	Example 1: Uplink received power	172
5.4.3	Example 2: Downlink received power	173
5.4.4	Additional losses	174
5.4.5	Conclusion	176
5.5	Noise power spectral density at the receiver input	176
5.5.1	The origins of noise	176
5.5.2	Noise characterisation	177
5.5.3	Noise temperature of an antenna	180
5.5.4	System noise temperature	185
5.5.5	System noise temperature: Example	186
5.5.6	Conclusion	186
5.6	Individual link performance	186
5.6.1	Carrier power to noise power spectral density ratio at receiver input	187
5.6.2	Clear sky uplink performance	187
5.6.3	Clear sky downlink performance	189
5.7	Influence of the atmosphere	193
5.7.1	Impairments caused by rain	193
5.7.2	Other impairments	207
5.7.3	Link impairments—relative importance	209

5.7.4	Link performance under rain conditions	209
5.7.5	Conclusion	210
5.8	Mitigation of atmospheric impairments	210
5.8.1	Depolarisation mitigation	210
5.8.2	Attenuation mitigation	211
5.8.3	Site diversity	211
5.8.4	Adaptivity	212
5.8.5	Cost-availability trade-off	212
5.9	Overall link performance with transparent satellite	213
5.9.1	Characteristics of the satellite channel	214
5.9.2	Expression for $(C/N_0)_T$	218
5.9.3	Overall link performance for a transparent satellite without interference or intermodulation	221
5.10	Overall link performance with regenerative satellite	225
5.10.1	Linear satellite channel without interference	226
5.10.2	Non-linear satellite channel without interference	227
5.10.3	Non-linear satellite channel with interference	228
5.11	Link performance with multibeam antenna coverage vs monobeam coverage	230
5.11.1	Advantages of multibeam coverage	231
5.11.2	Disadvantages of multibeam coverage	234
5.11.3	Conclusion	237
5.12	Intersatellite link performance	237
5.12.1	Frequency bands	238
5.12.2	Radio-frequency links	238
5.12.3	Optical links	239
5.12.4	Conclusion	245
	References	246
6	MULTIPLE ACCESS	247
6.1	Layered data transmission	247
6.2	Traffic parameters	248
6.2.1	Traffic intensity	248
6.2.2	Call blocking probability	248
6.2.3	Burstiness	248
6.3	Traffic routing	249
6.3.1	One carrier per station-to-station link	250
6.3.2	One carrier per transmitting station	251
6.3.3	Comparison	251
6.4	Access techniques	251
6.4.1	Access to a particular satellite channel (or transponder)	251
6.4.2	Multiple access to the satellite channel	252
6.4.3	Performance evaluation—efficiency	253
6.5	Frequency division multiple access (FDMA)	253
6.5.1	TDM/PSK/FDMA	254
6.5.2	SCPC/FDMA	254
6.5.3	Adjacent channel interference	254
6.5.4	Intermodulation	254
6.5.5	FDMA efficiency	258
6.5.6	Conclusion	260

6.6	Time division multiple access (TDMA)	260
6.6.1	Burst generation	260
6.6.2	Frame structure	262
6.6.3	Burst reception	264
6.6.4	Synchronisation	265
6.6.5	TDMA efficiency	270
6.6.6	Conclusion	271
6.7	Code division multiple access (CDMA)	272
6.7.1	Direct sequence (DS-CDMA)	273
6.7.2	Frequency hopping CDMA (FH-CDMA)	276
6.7.3	Code generation	277
6.7.4	Synchronisation	278
6.7.5	CDMA efficiency	280
6.7.6	Conclusion	281
6.8	Fixed and on-demand assignment	283
6.8.1	The principle	283
6.8.2	Comparison between fixed and on-demand assignment	283
6.8.3	Centralised or distributed management of on-demand assignment	284
6.8.4	Conclusion	284
6.9	Random access	285
6.9.1	Asynchronous protocols	286
6.9.2	Protocols with synchronisation	289
6.9.3	Protocols with assignment on demand	290
6.10	Conclusion	290
References		291
7	SATELLITE NETWORKS	293
7.1	Network reference models and protocols	293
7.1.1	Layering principle	293
7.1.2	Open Systems Interconnection (OSI) reference model	294
7.1.3	IP reference model	295
7.2	Reference architecture for satellite networks	296
7.3	Basic characteristics of satellite networks	298
7.3.1	Satellite network topology	298
7.3.2	Types of link	300
7.3.3	Connectivity	300
7.4	Satellite on-board connectivity	302
7.4.1	On-board connectivity with transponder hopping	302
7.4.2	On-board connectivity with transparent processing	303
7.4.3	On-board connectivity with regenerative processing	308
7.4.4	On-board connectivity with beam scanning	313
7.5	Connectivity through intersatellite links (ISL)	314
7.5.1	Links between geostationary and low earth orbit satellites (GEO-LEO)	314
7.5.2	Links between geostationary satellites (GEO-GEO)	314
7.5.3	Links between low earth orbit satellites (LEO-LEO)	318
7.5.4	Conclusion	319
7.6	Satellite broadcast networks	319
7.6.1	Single uplink (one programme) per satellite channel	320
7.6.2	Several programmes per satellite channel	321
7.6.3	Single uplink with time division multiplex (TDM) of programmes	321
7.6.4	Multiple uplinks with time division multiplex (TDM) of programmes on downlink	322

7.7	Broadband satellite networks	322
7.7.1	Overview of DVB-RCS and DVB-S/S2 network	324
7.7.2	Protocol stack architecture for broadband satellite networks	325
7.7.3	Physical layer	326
7.7.4	Satellite MAC layer	333
7.7.5	Satellite link control layer	338
7.7.6	Quality of service	340
7.7.7	Network layer	343
7.7.8	Regenerative satellite mesh network architecture	346
7.8	Transmission control protocol	351
7.8.1	TCP segment header format	351
7.8.2	Connection set up and data transmission	352
7.8.3	Congestion control and flow control	353
7.8.4	Impact of satellite channel characteristics on TCP	354
7.8.5	TCP performance enhancement	355
7.9	IPv6 over satellite networks	356
7.9.1	IPv6 basics	357
7.9.2	IPv6 transitions	358
7.9.3	IPv6 tunnelling through satellite networks	358
7.9.4	6to4 translation via satellite networks	359
7.10	Conclusion	359
	References	360
8	EARTH STATIONS	363
8.1	Station organisation	363
8.2	Radio-frequency characteristics	364
8.2.1	Effective isotropic radiated power (EIRP)	364
8.2.2	Figure of merit of the station	366
8.2.3	Standards defined by international organisations and satellite operators	366
8.3	The antenna subsystem	376
8.3.1	Radiation characteristics (main lobe)	379
8.3.2	Side-lobe radiation	379
8.3.3	Antenna noise temperature	380
8.3.4	Types of antenna	385
8.3.5	Pointing angles of an earth station antenna	390
8.3.6	Mountings to permit antenna pointing	393
8.3.7	Tracking	399
8.4	The radio-frequency subsystem	408
8.4.1	Receiving equipment	408
8.4.2	Transmission equipment	411
8.4.3	Redundancy	417
8.5	Communication subsystems	417
8.5.1	Frequency translation	418
8.5.2	Amplification, filtering and equalisation	420
8.5.3	Modems	421
8.6	The network interface subsystem	425
8.6.1	Multiplexing and demultiplexing	425
8.6.2	Digital speech interpolation (DSI)	426
8.6.3	Digital circuit multiplication equipment (DCME)	427
8.6.4	Echo suppression and cancellation	430
8.6.5	Equipment specific to SCPC transmission	432

8.7	Monitoring and control; auxiliary equipment	432
8.7.1	Monitoring, alarms and control (MAC) equipment	432
8.7.2	Electrical power	432
8.8	Conclusion	433
References		434
9	THE COMMUNICATION PAYLOAD	435
9.1	Mission and characteristics of the payload	435
9.1.1	Functions of the payload	435
9.1.2	Characterisation of the payload	436
9.1.3	The relationship between the radio-frequency characteristics	437
9.2	Transparent repeater	437
9.2.1	Characterisation of non-linearities	438
9.2.2	Repeater organisation	447
9.2.3	Equipment characteristics	453
9.3	Regenerative repeater	465
9.3.1	Coherent demodulation	465
9.3.2	Differential demodulation	466
9.3.3	Multicarrier demodulation	466
9.4	Multibeam antenna payload	467
9.4.1	Fixed interconnection	467
9.4.2	Reconfigurable (semi-fixed) interconnection	468
9.4.3	Transparent on-board time domain switching	468
9.4.4	On-board frequency domain transparent switching	471
9.4.5	Baseband regenerative switching	472
9.4.6	Optical switching	475
9.5	Introduction to flexible payloads	475
9.6	Solid state equipment technology	477
9.6.1	The environment	477
9.6.2	Analogue microwave component technology	477
9.6.3	Digital component technology	478
9.7	Antenna coverage	479
9.7.1	Service zone contour	479
9.7.2	Geometrical contour	482
9.7.3	Global coverage	482
9.7.4	Reduced or spot coverage	484
9.7.5	Evaluation of antenna pointing error	486
9.7.6	Conclusion	498
9.8	Antenna characteristics	498
9.8.1	Antenna functions	498
9.8.2	The radio-frequency coverage	500
9.8.3	Circular beams	501
9.8.4	Elliptical beams	504
9.8.5	The influence of depointing	505
9.8.6	Shaped beams	507
9.8.7	Multiple beams	510
9.8.8	Types of antenna	511
9.8.9	Antenna technologies	515
9.9	Conclusion	524
References		524

10	THE PLATFORM	527
10.1	Subsystems	528
10.2	Attitude control	529
10.2.1	Attitude control functions	530
10.2.2	Attitude sensors	531
10.2.3	Attitude determination	532
10.2.4	Actuators	534
10.2.5	The principle of gyroscopic stabilisation	536
10.2.6	Spin stabilisation	540
10.2.7	'Three-axis' stabilisation	541
10.3	The propulsion subsystem	547
10.3.1	Characteristics of thrusters	547
10.3.2	Chemical propulsion	549
10.3.3	Electric propulsion	553
10.3.4	Organisation of the propulsion subsystem	558
10.3.5	Electric propulsion for station keeping and orbit transfer	561
10.4	The electric power supply	562
10.4.1	Primary energy sources	562
10.4.2	Secondary energy sources	567
10.4.3	Conditioning and protection circuits	574
10.4.4	Example calculations	578
10.5	Telemetry, tracking and command (TTC) and on-board data handling (OBDH)	580
10.5.1	Frequencies used	581
10.5.2	The telecommand links	581
10.5.3	Telemetry links	582
10.5.4	Telecommand (TC) and telemetry (TM) message format standards	583
10.5.5	On-board data handling (OBDH)	588
10.5.6	Tracking	593
10.6	Thermal control and structure	596
10.6.1	Thermal control specifications	597
10.6.2	Passive control	598
10.6.3	Active control	601
10.6.4	Structure	601
10.6.5	Conclusion	603
10.7	Developments and trends	604
	References	606
11	SATELLITE INSTALLATION AND LAUNCH VEHICLES	607
11.1	Installation in orbit	607
11.1.1	Basic principles	607
11.1.2	Calculation of the required velocity increments	609
11.1.3	Inclination correction and circularisation	610
11.1.4	The apogee (or perigee) motor	617
11.1.5	Injection into orbit with a conventional launcher	622
11.1.6	Injection into orbit from a quasi-circular low altitude orbit	626
11.1.7	Operations during installation (station acquisition)	627
11.1.8	Injection into orbits other than geostationary	630
11.1.9	The launch window	631
11.2	Launch vehicles	631
11.2.1	Brazil	632
11.2.2	China	635

11.2.3	Commonwealth of Independent States (CIS)	636
11.2.4	Europe	641
11.2.5	India	648
11.2.6	Israel	648
11.2.7	Japan	649
11.2.8	South Korea	652
11.2.9	United States of America	652
11.2.10	Reusable launch vehicles	660
11.2.11	Cost of installation in orbit	661
	References	661
12 THE SPACE ENVIRONMENT		663
12.1	Vacuum	663
12.1.1	Characterisation	663
12.1.2	Effects	663
12.2	The mechanical environment	664
12.2.1	The gravitational field	664
12.2.2	The earth's magnetic field	665
12.2.3	Solar radiation pressure	666
12.2.4	Meteorites and material particles	667
12.2.5	Torques of internal origin	667
12.2.6	The effect of communication transmissions	668
12.2.7	Conclusions	668
12.3	Radiation	668
12.3.1	Solar radiation	669
12.3.2	Earth radiation	671
12.3.3	Thermal effects	671
12.3.4	Effects on materials	672
12.4	Flux of high energy particles	672
12.4.1	Cosmic particles	672
12.4.2	Effects on materials	674
12.5	The environment during installation	675
12.5.1	The environment during launching	676
12.5.2	Environment in the transfer orbit	677
	References	677
13 RELIABILITY OF SATELLITE COMMUNICATIONS SYSTEMS		679
13.1	Introduction of reliability	679
13.1.1	Failure rate	679
13.1.2	The probability of survival or reliability	680
13.1.3	Failure probability or unreliability	680
13.1.4	Mean time to failure (MTTF)	682
13.1.5	Mean satellite lifetime	682
13.1.6	Reliability during the wear-out period	682
13.2	Satellite system availability	683
13.2.1	No back-up satellite in orbit	683
13.2.2	Back-up satellite in orbit	684
13.2.3	Conclusion	684
13.3	Subsystem reliability	685
13.3.1	Elements in series	685

13.3.2	Elements in parallel (static redundancy)	685
13.3.3	Dynamic redundancy (with switching)	687
13.3.4	Equipment having several failure modes	690
13.4	Component reliability	691
13.4.1	Component reliability	691
13.4.2	Component selection	692
13.4.3	Manufacture	693
13.4.4	Quality assurance	693
INDEX		697

ACKNOWLEDGEMENT

Reproduction of figures extracted from the 1990 Edition of CCIR Volumes (XVIIth Plenary Assembly, Düsseldorf, 1990), the *Handbook on Satellite Communications* (ITU Geneva, 1988) and the ITU-R Recommendations is made with the authorisation of the International Telecommunication Union (ITU) as copyright holder.

The choice of the excerpts reproduced remains the sole responsibility of the authors and does not involve in any way the ITU.

The complete ITU documentation can be obtained from:

**International Telecommunication Union
General Secretariat, Sales Section
Place des Nations, 1211 GENEVA 20, Switzerland**

Tel: +41 22 730 51 11 **Tg:** Burinterna Geneva
Telefax: + 41 22 730 51 94 **Tlx:** 421 000 uit ch

ACRONYMS

AAL	ATM Adaptation Layer	ARTES	Advanced Research in Telecommunications Systems (ESA programme)
A/D	Analog-to-Digital conversion		
ABCS	Advanced Business Communications via Satellite	ASCII	American Standard Code for Information Interchange
ABM	Apogee Boost Motor	ASIC	Application Specific Integrated Circuit
ACD	Average Call Distance	ASN	Acknowledgement Sequence Number
ACI	Adjacent Channel Interference	ASN	Abstract Syntax Notation
ACK	ACKnowledgement	ASTE	Advanced Systems and Telecommunications Equipment (ESA programme)
ACTS	Advanced Communications Technology Satellite		
ADC	Analog to Digital Converter	ASTP	Advanced Systems and Technology Programme (ESA programme)
ADM	Adaptive Delta Modulation	ASYNC	ASYNChronous data transfer
ADPCM	Adaptive Pulse Code Modulation	ATA	Auto-Tracking Antenna
ADSL	Asymmetric Digital Subscriber Line	ATC	Adaptive Transform Coding
AES	Audio Engineering Society	ATM	Asynchronous Transfer Mode
AGCH	Access Granted CHannel		
AKM	Apogee Kick Motor	BAPTA	Bearing and Power Transfer Assembly
ALC	Automatic Level Control	BCH	Broadcast Channel
ALG	Application Level Gateway	BCR	Battery Charge Regulator
AM	Amplitude Modulation	BDR	Battery Discharge Regulator
AMAP	Adaptive Mobile Access Protocol	BECN	Backward explicit congestion notification
AMP	AMPlifier	BEP	Bit Error Probability
AMPS	Advanced Mobile Phone Service	BER	Bit Error Rate
AMSC	American Mobile Satellite Corp.	BFN	Beam Forming Network
AMSS	Aeronautical Mobile Satellite Service	BFSK	Binary Frequency Shift Keying
ANSI	American National Standards Institute	BGMP	Border Gateway Multicast Protocol
AOCS	Attitude and Orbit Control System	BGP	Border Gateway Protocol
AOM	Administration, Operation and Maintenance	BHCA	Busy Hour Call Attempts
AOR	Atlantic Ocean Region	BHCR	Busy Hour Call Rate
APC	Adaptive Predictive Coding	BISDN	Broadband ISDN
APD	Avalanche Photodetector	BIS	Broadband Interactive System
API	Application Programming Interface	BITE	Built-In Test Equipment
AR	Axial Ratio	BOL	Beginning of Life
ARQ	Automatic Repeat Request	BPF	Band Pass Filter
ARQ-GB(N)	Automatic repeat ReQuest-Go Back N	BPSK	Binary Phase Shift Keying
ARQ-SR	Automatic repeat ReQuest-Selective Repeat	BS	Base Station
ARCS	Astra Return Channel System		
ARQ-SW	Automatic repeat ReQuest-Stop and Wait		

BSC	Binary Synchronous Communications (bisync)	CNES	Centre National d'Etudes Spatiales (French Space Agency)
BSN	Block Sequence Number	CODLS	Connection Oriented Data Link Service
BSS	Broadcasting Satellite Service	COMETS	Communications and Broadcasting Engineering Test Satellite
BT	Base Transceiver	CONUS	CONTinental US
BTS	Base Transceiver Station	CoS	Class of Service
BW	BandWidth	COST	European COoperation in the field of Scientific and Technical research
CAD	Computer Aided Design	COTS	Commercial Off The Shelf
CAM	Computer Aided Manufacturing	CPS	Chemical Propulsion System
CAMP	Channel AMPLifier	CRC	Communications Research Centre (Canada)
CATV	CABleTelevision	CS	Cell Selection
CBDS	Connectionless broadband data service	CSMA	Carrier Sense Multiple Access
CBO	Continuous Bit Oriented	CT	Cordless Telephone
CBR	Constant Bit Rate	CTR	Common Technical Regulation
CCI	CoChannel Interference	CTU	Central Terminal Unit
CCIR	Comité Consultatif International des Radiocommunications (International Radio Consultative Committee)	D-AMPS	Digital Advanced Mobile Phone System
CCITT	Comité Consultatif International du Télégraphe et du Téléphone (The International Telegraph and Telephone Consultative Committee)	D-M-PSK	Differential M-ary Phase Shift Keying
CCSDS	Consultative Committee for Space Data Systems	D/C	Down-Converter
CCU	Cluster Control Unit	DA	Demand Assignment
CDMA	Code Division Multiple Access	DAB	Digital Audio Broadcasting
CEC	Commission of the European Communities	DAC	Digital to Analog Converter
CELP	Code Excited Linear Prediction	DAMA	Demand Assignment Multiple Access
CENELEC	Comité Européen pour la Normalisation en ELECTrotechnique (European Committee for Electro-technical Standardisation)	DARPA	Defense Advanced Research Project
CEPT	Conférence Européenne des Postes et Télécommunications (European Conference of Post and Telecommunications)	DASS	Demand Assignment Signalling and Switching
CFDMA	Combined Free/Demand Assignment Multiple Access	dB	decibel
CFM	Companded Frequency Modulation	dBm	Unit for expression of power level in dB with reference to 1 mW
CFRA	Combined Fixed/Reservation Assignment	dBm	Unit for expression of power level in dB with reference to 1 mW
CIR	Committed Information Rate	dBmO	Unit for expression of power level in dBm at a point of zero relative level (a point of a telephone channel where the 800 Hz test signal has a power of 1 mW)
CIRF	Co-channel Interference Reduction Factor	DBF	Digital Beam Forming
CIS	Commonwealth of Independent States	DBFN	Digital Beam Forming Network
CLDLS	ConnectionLess Data Link Service	DBS	Direct Broadcasting Satellite
CLEC	Competitive Local Exchange Carrier	DC	Direct Current
CLNP	ConnectionLess Network Protocol	DCCH	Dedicated Control Channel
CLTU	Command Link Transmission Unit	DCE	Data Circuit Terminating Equipment
CMOS	Complementary Metal Oxide Semiconductor	DCFL	Direct Coupled Fet Logic
		DCME	Digital Circuit Multiplication Equipment
		DCS	Digital Cellular System (GSM At 1800 MHz)
		DCT	Discrete Cosine Transform
		DCU	Distribution Control Unit
		DDCMP	Digital Data Communications Message Protocol (a DEC Protocol)
		DE	Differentially Encoded

DE-M-PSK	Differentially Encoded M-ary Phase Shift Keying	EUTELSAT	European Telecommunications Satellite Organisation
DECT	Digital European Cordless Telephone	FAC	Final Assembly Code
DEMODO	DEMODulator	FCC	Federal Communications Commission
DEMUX	DEMUltipleXer	FCS	Frame Check Sequence
DES	Data Encryption Standard	FDDI	Fibre Distributed Data Interface
DM	Delta Modulation	FDM	Frequency Division Multiplex
DNS	Domain Name Service (host name resolution protocol)	FDMA	Frequency Division Multiple Access
DOD	Depth of Discharge	FEC	Forward Error Correction
DOF	Degree of Freedom	FES	Fixed Earth Station
DQDB	Distributed Queue Dual Bus	FET	Field Effect Transistor
DSCP	Differentiated Service Code Point	FETA	Field Effect Transistor Amplifier
DSI	Digital Speech Interpolation	FFT	Fast Fourier Transform
DSL	Digital Subscriber Loop	FGM	Fixed Gain Mode
DSP	Digital Signal Processing	FIFO	First In First Out
DTE	Data Terminating Equipment	FM	Frequency Modulation
DTH	Direct To Home	FMA	Fixed-Mount Antenna
DTTL	Data Transition Tracking Loop	FMS	Fleet Management Service
DUT	Device Under Test	FMT	Fade Mitigation Technique
DVB	Digital Video Broadcasting	FODA	FIFO Ordered Demand Assignment
DWDM	Dense Wave Division Multiplexing	FPGA	Field Programmable Gate Array
		FPLMTS	Future Public Land Mobile Telecommunications System
EA	Early Assignment	FS	Fixed Service
EBU	European Broadcasting Union	FR	Frame Relay
EC	European Community	FSK	Frequency Shift Keying
ECL	Emitter Coupled Logic	FSS	Fixed Satellite Service
EFS	Error Free Seconds	FTP	File Transfer Protocol
EIA	Electronic Industries Association		
EIR	Equipment Identity Register	GA	ETSI General Assembly
EIRP	Effective Isotropic Radiated Power (W)	GaAs	Gallium Arsenide
ELSR	Edge Label Switch Router	GBN	Go Back N
EMC	ElectroMagnetic Compatiblity	GC	Global Coverage
EMF	ElectroMagnetic Field	GCE	Ground Communication Equipment
EMI	ElectroMagnetic Interference	GCS	Ground Control Station
EMS	European Mobile Satellite	GDE	Group Delay Equalizer
ENR	Excess Noise Ratio	GEO	Geostationary Earth Orbit
EOL	End of Life	GMDSS	Global Maritime Distress and Safety System
EPC	Electric Power Conditioner	GOS	Grade Of Service
EPIRB	Emergency Position Indicating Radio Beam	GPRS	General Packet Radio Service
ERC	European Radiocommunications Committee	GPS	Global Positioning System
ERL	Echo Return Loss	GRE	Generic Routing Encapsulation
ERO	European Radiocommunications Office (of the ERC)	GSM	Global System for Mobile communications
ES	Earth Station	GSO	Geostationary Satellite Orbit
ESA	European Space Agency	GTO	Geostationary Transfer Orbit
ESTEC	European Space Research and Technology Centre		
ETR	ETSI Technical Report	HDB3	High Density Binary 3 code
ETS	European Telecommunications Standard, created within ETSI	HDLCL	High Level Data Link Control
		HDTV	High Definition TeleVision
		HEMT	High Electron Mobility Transistor
ETSI	European Telecommunications Standards Institute	HEO	Highly Elliptical Orbit
		HIO	Highly Inclined Orbit

HIPERLAN	High Performance Radio Local Area Network	ISO	International Organisation for Standardisation
HLR	Home Location Register	ISS	Inter-Satellite Service
HPA	High Power Amplifier	ISU	Iridium Subscriber Unit
HPB	Half Power Beamwidth	ITU	International Telecommunication Union
HPT	Hand Held Personal Telephone		
HTML	Hyper Text Markup Language	IUS	Inertial Upper Stage
HTTP	Hyper Text Transfer Protocol	IVOD	Interactive Video On Demand
		IWU	InternetWorking Unit
IAT	Interarrival Time		
IAU	International Astronomical Unit	JDBC	Java Database Connectivity
IBA	Independent Broadcasting Authority	JPEG	Joint Photographic Expert Group
IBO	Input Back-off		
IBS	International Business Service	LA	Location Area
ICMP	Internet Control Message Protocol	LAN	Local Area Network
ICI	Interface Control Information	LAPB	Link Access Protocol Balanced
ICO	Intermediate Circular Orbit	LDP	Label Distribution Protocol
IGMP	Internet Group Management Protocol	LEO	Low Earth Orbit
IDC	Intermediate rate Digital Carrier	LEFSR	Linear Feedback Shift Register
IDR	Intermediate Data Rate	LHCP	Left Hand Circular Polarization
IDU	Interface Data Unit, also. InDoor Unit	LLC	Logical Link Control
IEEE	Institute of Electrical and Electronic Engineers	LLM	Lband Land Mobile
		LMDS	Local Multipoint Distribution System
IETF	Internet Engineering Task Force	LMSS	Land Mobile Satellite Service
I-ETS	Interim ETS	LNA	Low Noise Amplifier
IF	Intermediate Frequency	LNB	Low Noise Block
IFRB	International Frequency Registration Board	LO	Local Oscillator
		LOS	Line of Sight
IGMP	Internet Group Management Protocol	LPC	Linear Predictive Coding
ILS	International Launch Services	LPF	Low Pass Filter
IM	InterModulation	LR	Location Register
IMP	Interface Message Processor	LRE	Low Rate Encoding
IMP	InterModulation Product	LSP	Label Switched Path
IMSI	International Mobile Subscriber Identity	LSR	Label Switching Router
		LU	Location Updating
IMUX	Input Multiplexer		
IN	Intelligent Network	M-PSK	M-ary Phase Shift Keying
INIRIC	International Non-Ionising Radiation Committee	MAC	Medium Access Control
		MAC	Multiplexed Analog Components (also Monitoring, Alarm and Control)
INMARSAT	International Maritime Satellite Organisation	MACSAT	Multiple Access Satellite
INTELSAT	International Telecommunications Satellite Consortium	MAMA	Multiple ALOHA Multiple Access
		MAN	Metropolitan Area Network
IOR	Indian Ocean Region	MCPC	Multiple Channels Per Carrier
IOT	In Orbit Test	MEB	Megabit Erlang Bit rate
IP	Internet Protocol (a network layer datagram protocol)	MEO	Medium altitude Earth Orbit
		MES	Mobile Earth Station
IPA	Intermediate Power Amplifier	MESFET	Metal Semiconductor Field Effect Transistor
IPE	Initial Pointing Error		
IPsec	IP security policy	MF	Multifrequency
IRCD	Internet Relay Chat Program Server (a teleconferencing application)	MHT	Mean Holding Time
		MIC	Microwave Integrated Circuit
IRD	Internet Resources Database	MIDI	Musical Instrument Digital Interface
IRD	Integrated Receiver Decoder	MIFR	Master International Frequency Register
ISDN	Integrated Services Digital Network		
ISC	International Switching Center	MMDS	Multipoint Multichannel Distribution System
ISL	Intersatellite Link		

MMIC	Monolithic Microwave Integrated Circuit	PB	Primary Body (orbits)
MOD	MODulator	PBX	Private (automatic) Branch eXchange
MODEM	Modulator/Demodulator	PC	Personal Computer
MOS	Mean Opinion Score	PCCH	Physical Control CHannel
MOS	Metal-Oxide Semiconductor	PCH	Paging CHannel
MoU	Memorandum of Understanding	PCM	Pulse Code Modulation
MPEG	Motion Picture Expert Group	PCN	Personal Communications Network (often refers to DCS 1800)
MPLS	Multi-Protocol Label Switching	PCS	Personal Communications System
MPSK	M-ary Phase Shift Keying	PDCH	Physical Data CHannel
MS	Mobile Station	PDF	Probability Density Function
MSC	Mobile Switching Center	PDH	Plesiochronous Digital Hierarchy
MSK	Minimum Shift Keying	PDU	Protocol Data Unit
MSS	Mobile Satellite Service	PDF	Power Flux Density
MTBF	Mean Time Between Failure	PHEMT	Pseudomorphic High Electron Mobility Transistor
MTP	Message Transfer Part	PHB	Per Hop Behaviour
MTU	Maximum Transferable Unit	PHP	Personal Handy Phone
MUX	MULTipleXer	PHS	Personal Handyphone System
MX	MiXer	PICH	Pilot Channel
NACK	No ACKnowledgment	PILC	Performance Implication of Link Characteristics
NASA	National Aeronautics And Space Administration (USA)	PIMP	Passive InterModulation Product
NASDA	National Aeronautics And Space Development Agency (Japan)	PKM	Perigee Kick Motor
NAT	Network Address Translation	PLL	Phase Locked Loop
NGSO	Non-Geostationary Satellite Orbit	PLMN	Public Land Mobile Network
NH	Northern Hemisphere	PM	Phase Modulation
NIS	Network Information System	PMR	Private Mobile Radio
NMT	Nordic Mobile Telephone	PN	Personal Number
NNTP	Network News Transfer Protocol	PODA	Priority Oriented Demand Assignment
NOAA	National Oceanic and Atmospheric Administration	POL	POLarisation
NORM	Nack-Oriented Reliable Multicast	POR	Pacific Ocean Region
NSO	National Standardisation Organisation	PP	Portable Part
NRZ	Non-Return to Zero	PPP	Point to Point Protocol
NTP	Network Time Protocol	PRMA	Packet Reservation Multiple Access
NVOD	Near Video On Demand	PSD	Power Spectral Density
OACSU	Off-Air Call Set-Up	PSK	Phase Shift Keying
OBC	On-Board Computer	PSPDN	Packet Switched Public Data Network
OBO	Output Back-Off	PSTN	Public Switched Telephone Network
OBP	On-Board Processing	PTA	Programme Tracking Antenna
ODU	Outdoor Unit	PTN	Public Telecommunications Network
OICETS	Optical Inter-orbit Communications Engineering Test Satellite	PTO	Public Telecommunications Operator
OMUX	Output MULTipleXer	PVA	Perigee Velocity Augmentation
ONP	Open Network Provision	PVC	Permanent Virtual Circuit
OSI	Open System Interconnection	QoS	Quality of Service
OSPF	Open Shortest Path First	QPSK	Quaternary Phase Shift Keying
PABX	Private Automatic Branch eXchange	RAAN	Right Ascension of the Ascending Node
PACS	Personal Access Communications System	RACE	Research and development in Advanced Communications
PAD	Packet Assembler/Disassembler	RACH	Random Access Channel
PAM	Payload Assist Module	RADIUS	Remote Authentication Dial In User Service
		RAM	Random Access Memory

RAN	Radio Area Network	SFH	Slow Frequency Hopping
RARC	Regional Administrative Radio Conference	SH	Southern Hemisphere
		SHF	Super High Frequency (3 GHz to 30 GHz)
RAS	Radio Astronomy Service		
RCVO	Receive Only	SIM	Subscriber Identity Module
RCVR	ReCeIveR	S-ISUP	Satellite ISDN User Part
RDS	Radio Data System	SIT	Satellite Interactive Terminal
RDSS	Radio Determination Satellite Service	SKW	Satellite-Keeping Window
RE	Radio Exchange	SL	Satellite
Rec	Recommendation	SLA	Service Level Agreement
Rep	Report	SLIC	Subscriber Line Interface Card
RES	Radio Equipment Systems, ETSI Technical Committee	SMATV	Satellite based Master Antenna for TV distribution
RF	Radio Frequency	SME	Small and Medium Enterprise
RFHMA	Random Frequency Hopping Multiple Access	SMS	Satellite Multi-Services
		SMTP	Simple Mail Transfer Protocol
RFI	Radio Frequency Interference	SNA	Systems Network Architecture (IBM)
RGS	Route Guidance Service	SNDCP	SubNet Dependent Convergence Protocol
RHCP	Right-Hand Circular Polarization		
RIP	Routing Information Protocol	SNEK	Satellite NETworK node computer
RL	Return Loss	SNG	Satellite News Gathering
RLAN	Radio Local Area Network	SNMP	Simple Network Management Protocol
RLL	Radio in the Local Loop		
RLOGIN	Remote login application	SNR	Signal-to-Noise Ratio
RMA	Random Multiple Access	SOC	State of Charge
RMTP	Realisable Multicast Transport Protocol	SOHO	Small Office Home Office
		SORA	Satellite Oriented Resource Allocation
RNCC	Regional Network Control Center		
RNR	Receiver Not Ready	SORF	Start of Receive Frame
RORA	Region Oriented Resource Allocation	SOTF	Start of Transmit Frame
RR	Radio Regulation	SPADE	Single-channel-per-carrier PCM multiple Access Demand assignment Equipment
RS	Reed Solomon (coding)		
RSVP	Resource reSerVation Protocol		
RTCP	Real Time transport Control Protocol	S-PCN	Satellite Personal Communications Network
RTP	Real Time transport Protocol		
RTU	Remote Terminal Unit	S/PDIF	Sony/Philips Digital Interface Format
RX	Receiver	SPDT	Single-Pole Double-Throw (switch)
		SPMT	Single-Pole Multiple-Throw (switch)
S-ALOHA	Slotted ALOHA protocol	SPT	Stationary Plasma Thruster
SAMA	Spread ALOHA Multiple Access	SPU	Satellite Position Uncertainty
SAP	Service Access Point	SR	Selective Repeat
SAW	Surface Acoustic Wave	SS	Satellite Switch
SB	Secondary Body (orbits)	SSB	Single Side-Band
SBC	Sub-Band Coding	SSMA	Spread Spectrum Multiple Access
SC	Suppressed Carrier	SSO	Sun-Synchronous Orbit
S/C	SpaceCraft	SSOG	Satellite Systems Operations Guide (INTELSAT)
SCADA	Supervisory Control and Data Acquisition	SSP	Signalling Switching Point
SCCP	Signalling Connection Control Part	SSPA	Solid State Power Amplifier
SCH	Synchronization CHannel	SS-TDMA	Satellite Switched TDMA
SCP	Service Control Point	STC	ETSI Sub-Technical Committee
SCPC	Single Channel Per Carrier	STM	Synchronous Transport Module
SDH	Synchronous Digital Hierarchy	STS	Space Transportation System
SDLC	Synchronous Data Link Control	SU	Subscriber Unit
SDU	Service Data Unit	SVC	Switched Virtual Circuit
SEP	Symbol Error Probability	SW	Switch
SEU	Single Event Upset		

SW	Stop and Wait	UMTS	Universal Mobile Telecommunications System
SWR	Standing Wave Ratio		
SYNC	SYNChronisation	UPS	Uninterruptible Power Supply
		UPT	Universal Personal Telecommunications
TA	ETSI Technical Assembly		
TACS	Total Access Communication System	USAT	Ultra Small Aperture Terminal
TBC	To Be Confirmed	USB	Universal Serial Bus
TBD	To Be Defined	UW	Unique Word
TBR	Technical Basis Regulation		
T/R	Transmit/Receive	VBR	Variable Bit Rate
TC	Telecommand	VC	Virtual Channel (or Container)
TCH	Traffic CHannel	VCI	Virtual Channel Identifier
TCP	Transmission Control Protocol	VDSL	Very high-speed Digital Subscriber Line
TDM	Time Division Multiplex		
TDMA	Time Division Multiple Access	VHDL	VHSIC Hardware Description Language
TDRS	Tracking and Data Relay Satellite		
TELNET	remote terminal application	VHSIC	Very High Speed Integrated Circuit
TEM	Transverse ElectroMagnetic		
TETRA	Trans European Trunk Radio	VHF	Very High Frequency (30 MHz to 300 MHz)
TFTS	Terrestrial Flight Telephone System		
TIA	Telecommunications Industry Association	VLR	Visitor Location Register
		VLSI	Very Large Scale Integration
TIE	Terrestrial Interface Equipment	VOW	Voice Order Wire
TM	Telemetry	VPA	Variable Power Attenuator
TM/TC	Telemetry/Telecommand	VPC	Virtual Path Connection
TP4	Transport Protocol Class 4	VPD	Variable Phase Divider
TPR	Transponder	VPS	Variable Phase Shifter
TRAC	Technical Recommendations Application Committee	VPI	Virtual Path Identifier
		VPN	Virtual Private Network
TTC	Telemetry, Tracking and Command	VSAT	Very Small Aperture Terminal
TTCM	Telemetry, Tracking, Command and Monitoring	VSELP	Vector Sum Excitation Linear Prediction
TTL	Transistor Transistor Logic		
TTL	Time To Live	VSWR	Voltage Standing Wave Ratio
TTY	TelegraphY		
TV	TeleVision	WAN	Wide Area Network
TWT	Travelling WaveTube	WAP	Wireless Application Protocol
TWTA	Travelling WaveTube Amplifier	WARC	World Administrative Radio Conference
Tx	Transmitter	Web	Worldwide Web
U/C	Up-Converter		
UDLR	UniDirectional Link Routing	XPD	Cross Polarization Discrimination
UDP	User Datagram Protocol		
UHF	Ultra High Frequency (300 MHz to 3 GHz)	XPI	Cross Polarisation Isolation
		Xponder	Transponder

NOTATION

a	orbit semi-major axis	E	elevation angle (also energy and electric field strength)
A	azimuth angle (also attenuation, area, availability, traffic density and carrier amplitude)	E_b	energy per information bit
A_{eff}	effective aperture area of an antenna	E_c	energy per channel bit
A_{AG}	attenuation by atmospheric gases	f	frequency (Hz)
A_{RAIN}	attenuation due to precipitation and clouds	F_c	nominal carrier frequency
A_P	attenuation of radiowave by rain for percentage p of an average year	f_d	antenna focal length
B	bandwidth	f_m	frequency of a modulating sine wave
b	voice channel bandwidth (3100 Hz from 300 to 3400 Hz)	f_{max}	maximum frequency of the modulating baseband signal spectrum
B_n	noise measurement bandwidth at baseband (receiver output)	f_D	downlink frequency
B_N	equivalent noise bandwidth of receiver	f_U	uplink frequency
Bu	burstiness	F	noise figure
c	velocity of light = 3×10^8 m/s	ΔF_{max}	peak frequency deviation of a frequency modulated carrier
C	carrier power	f_s	sampling frequency
C/N_0	carrier power-to-noise power spectral density ratio (W/Hz)	g	peak factor
$(C/N_0)_U$	uplink carrier power-to-noise power spectral density ratio	G	power gain (also gravitational constant)
$(C/N_0)_D$	downlink carrier power-to-noise power spectral density ratio	G_{sat}	gain at saturation
$(C/N_0)_{\text{IM}}$	carrier power-to-intermodulation noise power spectral density ratio	G_R	receiving antenna gain in direction of transmitter
$(C/N_0)_I$	carrier power-to-interference noise power spectral density ratio	G_T	transmitting antenna gain in direction of receiver
$(C/N_0)_{\text{I,U}}$	uplink carrier power-to-interference noise power spectral density ratio	G_{Rmax}	maximum receiving antenna gain
$(C/N_0)_{\text{I,D}}$	downlink carrier power-to-interference noise power spectral density ratio	G_{Tmax}	maximum transmitting antenna gain
$(C/N_0)_T$	carrier power-to-noise power spectral density ratio for total link	G_{SR}	satellite repeater gain
D	diameter of a reflector antenna (also used as a subscript for 'downlink')	G_{SRsat}	saturation gain of satellite repeater
e	orbit eccentricity	G/T	gain to system noise temperature ratio of a receiving equipment
		G_{CA}	channel amplifier
		G_{FE}	front end gain from satellite receiver input to satellite channel amplifier input
		G_{ss}	small signal power gain
		i	inclination of the orbital plane
		k	Boltzmann's constant = 1.379×10^{-23} W/KHz
		k_{FM}	FM modulation frequency deviation constant (MHz/V)
		k_{PM}	PM phase deviation constant (rad/V)

K_P	AM/PM conversion coefficient	$P_{i\ n}$	input power in a multiple carrier operation mode (n carriers)
K_T	AM/PM transfer coefficient	$P_{o\ n}$	output power in a multiple carrier operation mode (n carriers)
l	earth station latitude	$P_{IMX\ n}$	power of intermodulation product of order X at output of a non-linear device in a multicarrier operation mode (n carriers)
L	earth station-to-satellite relative longitude also loss in link budget calculations, and loading factor of FDM/FM multiplex also message length (bits)	Q	quality factor
L_e	effective path length of radiowave through rain (km)	r	distance between centre of mass (orbits)
L_{FRX}	receiver feeder loss	R	slant range from earth station to satellite (km) (also symbol or bit rate)
L_{FTX}	transmitter feeder loss	R_b	information bit rate (s^{-1})
L_{FS}	free space loss	R_c	channel bit rate (s^{-1})
L_{POINT}	depointing loss	R_{call}	mean number of calls per unit time
L_{POL}	antenna polarisation mismatch loss	R_E	earth radius = 6378 km
L_R	receiving antenna depointing loss	R_o	geostationary satellite altitude = 35 786 km
L_T	transmitting antenna depointing loss	R_p	rainfall rate (mm/h) exceeded for time percentage p of a year
m	satellite mass	R_s	symbol (or signalling) rate (s^{-1})
mc	power reduction associated with multicarrier operation	S	user signal power (W)
M	mass of the earth (kg) (also number of possible states of a digital signal)	S/N	signal-to-noise power ratio at user's end
N_0	noise power spectral density (W/Hz)	T	period of revolution (orbits) (s) (also noise temperature (K))
$(N_0)_U$	uplink noise power spectral density (W/Hz)	T_A	antenna noise temperature (K)
$(N_0)_D$	downlink noise power spectral density (W/Hz)	T_{AMB}	ambient temperature (K)
$(N_0)_T$	total link noise power spectral density (W/Hz)	T_b	information bit duration (s)
$(N_0)_I$	interference power spectral density (W/Hz)	T_B	burst duration (s)
N	noise power (W) (also number of stations in a network)	T_c	channel bit duration (s)
p	pre-emphasis/companing improvement factor (also rainfall annual percentage)	T_e	effective input noise temperature of a four port element system (K)
p_w	rainfall worst month time percentage	T_E	mean sidereal day = 86164.15
P	power (also number of bursts in a TDMA frame)	T_{eATT}	effective input noise temperature of an attenuator (K)
P_b	information bit error rate	T_{eRX}	effective input noise temperature of a receiver
P_c	channel bit error rate	T_F	frame duration (s) (also feeder temperature)
P_{HPA}	rated power of high power amplifier (W)	T_m	effective medium temperature (K)
P_T	power fed to the antenna (W)	T_0	reference temperature (290 K)
P_{Tx}	transmitter power (W)	T_{eRX}	effective input noise temperature of a receiver (K)
P_R	received power (W)	T_S	symbol duration (s)
P_{RX}	power at receiver input (W)	T_{SKY}	clear key contribution to antenna noise temperature (K)
P_{is}	input power in a single carrier operation mode	T_{GROUND}	ground contribution to antenna noise temperature (K)
$P_{o\ 1}$	output power in a single carrier operation mode	U	subscript for 'uplink'
$(P_{i\ 1})_{sat}$	input power in a single carrier operation mode at saturation	v	true anomaly (orbits)
$(P_{o\ 1})_{sat}$	saturation output power in a single carrier operation mode	V_s	satellite velocity (m/s)

$V_{LP/P}$	peak-to-peak luminance voltage (V)		$G = 6.67 \times 10^{-11} \text{ m}^3 \text{ kg}^{-1} \text{ s}^{-2}$,
$V_{TP/P}$	peak-to-peak total video signal voltage (including synchronisation pulses)		$M = 5.974 \times 10^{24} \text{ kg}$;
V_{Nms}	root-mean-square noise voltage (V)	ρ	$\mu = GM = 3.986 \times 10^{14} \text{ m}^3 \text{ s}^{-2}$
w	psophometric weighting factor	σ	code rate
X	intermodulation product order (IMX)	ϕ	Stefan-Boltzmann constant = $5.67 \times 10^{-8} \text{ Wm}^{-2} \text{ K}^{-4}$
α	angle from boresight of antenna	Φ	satellite-earth station angle from the earth's centre
γ	vernal point	Φ_{\max}	power flux density (w/m^2)
Γ	spectral efficiency (bit/s Hz)	Φ_{nom}	max maximum power flux density at transmit antenna boresight
δ	declination angle (also delay)		nom nominal power flux density at receive end required to build up a given power assuming maximum receive gain (no depointing)
η	antenna aperture efficiency	Φ_{sat}	power flux density required to operate receive amplifier at saturation
λ	wavelength ($= c/f$) also longitude, also message generation rate (s^{-1})	ψ	polarisation angle
φ	latitude	ω	argument of perigee
τ	propagation time	Ω	right ascension of the ascending node
$\theta_{3\text{dB}}$	half power beamwidth of an antenna wavelength $= c/f$	Ω_E	angular velocity of rotation of the earth earth = $15.0469 \text{ deg/hr} =$ $4.17 \times 10^{-3} \text{ deg/s} = 7.292 \times 10^{-5} \text{ rad/s}$
θ_R	receiving antenna pointing error		
θ_T	transmit antenna pointing error		
μ	$= GM$ (G = gravitational constant, M = mass of earth;		

